

Sight glass - Tubular type

with Safety Seal-System, acc. to DIN 28121



Bauform 25-A

Application:

Sightglass - Tubular type with flanges on both sides, to use in either horizontal or vertical pipe lines for optical control of fluids and gasses.

Operating conditions:


Connection: Flanges acc 150 lbs
 Pressure: up to DN 100 - 6 bar max
 from DN 125 – 4 bar max
 Temperature: 200°C max.

Materials:

1. Flanges: WN 1.4571 | Steel H II
2. Distance-Bars: WN 1.4571 | Steel
5. Screws: A4-70 | Steel
3. Glass tube: Borosilicate glass (DURAN)
4. Gaskets: PTFE covered

Spezial designs:


Extra length
 Protection jacket of acrylic glass



Standard design

Mounting instructions:

Sight glass tubular type must be mounted without tension by tube, vibrations and pressure pushes.



Dimensions:

ANSI	D	BL
1"	108	160
1 1/2"	127	200
2"	152	230
3"	190	310
4"	228	350
5"	254	400
6"	279	480

Modifications reserved



AVEMAR cz s.r.o., Lihovarská 10, 716 03 Ostrava - Radvanice
 Tel.: +420 596 232 996, 596 232 997, Fax: +420 596 232 998
 E-mail: avemar@avemar.cz, web: www.avemar.cz