

www.phoenix-mt.com PHÖNIX Messtechnik GmbH.



Sight glass level gauge CL150 to 600		Product g	roup 7	700	
Light execution Reflex, Transparent Connection top-bottom pivoted		Туре		21	
Connection gauge valve to gauge chamber: union		Sheet: 19	Revision:	1	
Offset, handwheel		Date:	0	2/06	
	Direct read applications Increased sa General Visible length Body: Connection of Gauge valve Actuation: Material glas Material merc Depending of Types with s Hastelloy, Me Weight - basic weigh reflex / tran Depending of Design press - D40, reflex - 40 x 40, ref	A SL: 40 x 40, Ø4 gauge valve - body types: as plates acc. to DI dia wetted parts: on delivery situation pecial materials e. onel etc. are availant (glass type 4-9) sparent: (glass type 4-9) sparent: on execution weigh Data sure/-temperature dex, transparent:	epends on glass valves. AME - 1 40 (for special matrix) see data sheet hand (IN 7081: Bord IN 7081: Bord n material can va g. able5-14.0 kg / 13.2- 7.0-11.8 kg / 8.2- ti can vary. see data sheet E data sheet E data sheet E data sheet E	180 mr aterials unio 760.5 d whee osilicat CS, S ry. 17.5 k 12.8 k deratin 3G00R	
Orientation of gauge valve and operation	Process con		see 7	00.VA	
760.53 Orientation "0"	Vent: Drain:			00.VA	
top view	Accesso	ories			
side view pivoted	Glass protect Frosts protect Illumination: Scale: Heating:		see acce see acce see acce see acce see acce	essorie essorie essorie	
View direction View direction	type 316SS)	n steel) and SS (= are materials suita ording to EN or AS	able for Pressure ME.		
Ordering no.		Bučuv	Subject to alt	eratior	
see 700. 70021XX530XX-XX- (XXXXX)	K X X X - X X is from ME gla glass types gla DIN gau oriv	X X X Salzschli D-60386 Tel. +49/ Fax +49/ sales@p www.phc	hnik GmbH irfer Straße 13 5 Frankfurt/M. 69/41 67 42 - 20 /69/41 67 42 - 29 phoenix-mt.com enix-mt.com	X	